



MiCAT PLANNER

AUTOMATIC PART PROGRAM GENERATION



Part programs – easy, fast, automatic and reliable.

Traditionally, creating part programs for coordinate measuring machines is a strategic and time-consuming task.

Problems with conventional CMM part programming:

- Higher production costs. Misinterpretation of design intent may result in incorrect results leading to possible scrap.
- Lost productivity. Complex parts require time consuming path optimization.

 Lost productivity and higher production costs. The work of multiple part programmers can cause measurement discrepancies requiring investigation or possible scrap.
MiCAT Planner is the solution.



Your manufacturing processes need the ability to quickly adapt to meet today's challenging demands:

- Shorter product life cycles require rapid change to design revisions and fast programming capability.
- Increasing machine up-time requires more efficient programs and reduced set-up time.

Mitutoyo's CMM programming software, MiCAT Planner, meets all of these demands.





MiCAT Planner software by Mitutoyo generates CMM part programs with unprecedented efficiency.

MiCAT Planner drastically reduces programming efforts in developing part programs for coordinate measuring machines. The software's automatic measuring program generator saves time while reducing costs.

Features:

- MiCAT Planner identifies Geometric Dimensioning and Tolerancing (GD&T) from 3D models when included in the Product and Manufacturing Information (PMI), defines the measurement plan and automatically creates a measurement program.
- MiCAT Planner's integrated path and probe optimization function automatically selects the shortest measurement path with the fewest probe changes to measure the part in the least amount of time.
- MiCAT Planner's Rules Editor establishes consistent measurement guidelines to eliminate the variations that may occur between multiple CMM programmers.

PMI: CAD file containing GD&T information.



DME: Virtual model of the CMM includes all probe configurations.



User-defined rules determine the measurement strategy automatically for each feature.





Who can benefit from MiCAT Planner?

The Mitutoyo MiCAT Planner boasts amazing performance, speed and usability. So, the short answer is everyone can benefit from MiCAT Planner.



We only work on short or midsize runs. Is it really useful?

Yes, MiCAT Planner will dramatically reduce your programming time.

I only inspect outsourced parts and never evaluate the same characteristics. Is MiCAT Planner appropriate in this case?

Yes, MiCAT Planner will assist you in easily creating part programs that include different features and characteristics.

Our production is quite stable on long runs. We rarely need to create programs for new components on our CMM. Are you sure MiCAT Planner can help?

- Yes, MiCAT Planner ensures that all part programs are:
- Safe. Continuous collision detection and avoidance ensures operator safety and equipment integrity caused by costly probe collisions.
- Consistent. Rules Editor maintains uniform measurement guidelines for all components being inspected on the CMM.
- Optimization. Part measurement path is minimized to reduce inspection time and increase throughput.

We have many CMM programmers, why do we need MiCAT Planner?

MiCAT Planner's Rules Editor will ensure a higher level of quality in measurement programs so you can trust the program will always be developed using the same measuring practices, regardless of personal programming styles.

Regardless of the measuring tasks, MiCAT Planner adds an abundance of benefits to your CAD-based programming.

Graphical CMM Configuration



MiCAT Planner utilizes the CMM configuration's created with System Manager in the CMM MCOSMOS software. All racks and probes of the machine are graphically represented for the rack type and location on the CMM.





MiCAT Planner selects the most suitable probe configuration and measurement strategy for each feature implementing the best practices defined by User settings in the Rules Editor.

This virtual reality allows automatic avoidance of each rack zone. Even long styli can be avoided when positioned in the rack or encroaching in the measuring volume.

Measurement Strategy

One of the main benefits of MiCAT Planner is the compliance to measuring rules that can be set as needed.

Depending on the feature type, size or other criteria, you decide the number of measuring points, their distribution, and speed for touch-trigger or scanning probes.





Several sets of rules can be applied simultaneously according to manufacturing or customer requirements.

CAD Data Information: Automatic or Manual

After importing the CAD model, either all required features and GD&T are with the PMI data (Product Manufacturing Information), or can be manually input if the information is incomplete or not included.

> After a CAD model is loaded that includes PMI data, all required features and characteristics to be evaluated are instantly displayed and available, and a part program is automatically generated.





Automatic Part Program Generation



After all features and characteristics to be evaluated are validated and approved, a part program is automatically generated.

The Plan View (left) shows the outline of the measurement plan, where as the Program View (right) shows the measurement path and probing details. Both the Plan and Program views are synchronized with the 3D view (center). When you select a feature or characteristic in any of the three views, MiCAT Planner indicates the selected item in the other views.





If required, a missing feature (not identified on the CAD model) or a missing characteristic to be evaluated can be manually added from the 3D view.

Safe GD&T Interpretation

CAD-designed components are more and more defined by form and position symbols according to international standards.

However, depending on the individual programmer skill level, it may lead to different or inconsistent interpretation in the measurement strategy.





MiCAT Planner prevents risk of misinterpretation: each GD&T symbol, tolerance and datum is automatically understood and converted in the corresponding required measurement points. In the program view, all GD&T are shown in regards to the feature to be measured for calculating the result.

Cycle-Time Optimization

When programming manually, the programmer creates a measurement path following the required features for calculating the expected results.

Frequently, this results in unnecessary CMM movements and inefficient probing paths. Consequently, this results in longer inspection times that slow throughput and increase cost.

First, MiCAT Planner generates the probing path according to the measurement plan, and then optimizes it according to best strategy, avoiding wasted probe changes and/or movements.





MiCAT Planner automatically estimates the measuring cycle time according to the actual CMM configuration and settings. For example, the required time for exchanging a probe in the rack, or the specified scanning speed in your measurement rules, are considered for this time estimation. Immediately after the cycle optimization is executed, the new estimated cycle time is displayed.

... and much more.



Avoidance Zone

Several avoidance zones can be created to simulate the presence of any obstacle such as a clamp, a bracket or a column simulating a fixture.

MiCAT Planner will automatically calculate probing points and paths to avoid these areas, providing a collision-free part program.



Properties View			×
▲ General		100	
Nousire	9		
Norma	Moosuromont Point Sot 13		
Sampling method	Contact acarming		
Sampling pattern	Circles	•	
A Measurement tool			
Automatic	5		
Selected tool	PE A000 800 50%		
· Messurement strates	r.		
Number of circles	5		
Sampling interval	By pitch	•	
Som pitch	0 100		
Scan points per circle	100		
Edge offset	2 000		
Rotation	Clockwide		1
Negaurement direction	Aligned with feature axis		
Start angle	0 000000	_	
End atala	C 000000		
High speed scaming	P		

Individual Measurement Control

Any feature within the CAD model can be included or excluded from the Rules Editor, allowing for exceptions to define the measurement strategy when required by production or manufacturing requirements.

MiCAT Planner will consider this as an exception for a given feature, but will continue applying existing rules to all other features of this type.

Flexible Measurement Selection

While MiCAT Planner always selects the maximum number of features available to measure, the user can include or exclude features by checking / unchecking the corresponding boxes. Drag-and-drop functionality is also available for defining the measurement sequence.



-	-	HIGES	A 14 14 14 1 1
2.6	1	00000	58311125551n
Ĩ.	MICLAS	Dane Mark Million H.	COLORA DE LA COL
ſ		Ratio	Transfer Land Land Land Land Land Land Land Land
JE	1.0	Seering.	Two states a constant of the second states and a
31	1.56	Rind ted	14 centered art (19.000,000
12	4.35	Robust and	Protect to 18
E	1.34	which had	IN TRUCK IT WORKS & BRUNN
	1.78	Ring tol	The st \$1980 The S \$2000 Tree S \$1000
	1.30	Adres fort	Tuber partiets
12	1.35	Adapt last	8, M.M. 1, 18, 39 2 91, 91
85	0	Proprietal da	Algo northody upon all on mallet toporous (named to)a.g. for the advance addr.)
10	1.10	Description of the	

Edit Part Program

A part program generated by MiCAT Planner can be managed and edited using the MCOSMOS Editor.*

Return On Investment

Using MiCAT Planner means saving programming time, and time is money. But how much saving can you expect? Two different scenarios display your savings potential.

CAD model without PMI Data

Number of measured features	= 17		
Number of evaluated characteristics	= 22		
Programming time with MCOSMOS	= 51 minutes		
Programming time with MiCAT Planner	= 23 minutes		







CAD model with PMI Data

A CAD file with PMI that contains GD&T does not proportionally increase program generation time because of the number of features and characteristics.

In this example:

with MCOSMOS = 43 minutes with MiCAT Planner = 3 minutes



Supported Hardware



Mitutoyo CMMs

CRYSTA series STRATO series LEGEX series MACH-3A MACH-V



SP80

• TP200/TP20/TP2

• TP7M

Contact scanning probes

- MPP310/MPP100
- SP25M
- SP600M/SP600Q
- SP80

Probe head

- PH10M/PH10MQ/PH10T
- PH6M

Auto-change racks

- ACR3 (4 ports/8 ports)
- FCR25
- MCR20
- SCR200
- SCR600
- SCR6
- SCP80





Whatever your challenges are, Mitutoyo supports you from start to finish.

Mitutoyo is not only a manufacturer of top quality measuring products but one that also offers qualified support for the lifetime of the equipment, backed up by comprehensive services that ensure your staff can make the very best use of the investment.

Apart from the basics of calibration and repair, Mitutoyo offers product and metrology training, as well as IT support for the sophisticated software used in modern measuring technology. We can also design, build, test and deliver measuring solutions and even, if deemed cost-effective, take your critical measurement challenges in-house on a sub-contract basis.



Find additional product literature and our product catalog

www.mitutoyo.com

Note: All information regarding our products, and in particular the illustrations, drawings, dimensional and performance data contained in this printed matter as well as other technical data are to be regarded as approximate average values. We therefore reserve the right to make changes to the corresponding designs. The stated standards, similar technical regulations, descriptions and illustrations of the products were valid at the time of printing. In addition, the latest applicable version of our General Trading Conditions will apply. Only quotations submitted by ourselves may be regarded as definitive. Specifications are subject to change without notice.

Mitutoyo products are subject to US Export Administration Regulations (EAR). Re-export or relocation of our products may require prior approval by an appropriate governing authority.

Trademarks and Registrations Designations used by companies to distinguish their products are often claimed as trademarks. In all instances where Mitutoyo America Corporation is aware of a claim, the product names appear in initial capital or all capital letters. The appropriate companies should be contacted for more complete trademark and registration information.

Mitutoy

Mitutoyo America Corporation

www.mitutoyo.com One Number to Serve You Better 1-888-MITUTOYO (1-888-648-8869)

M³ Solution Centers:

Aurora, Illinois (Headquarters) Boston, Massachusetts Huntersville, North Carolina Mason, Ohio Plymouth, Michigan City of Industry, California Birmingham, Alabama Renton, Washington Houston, Texas